

Polaris HP S

Biostimulation laser therapy High power laser therapy

+ superpulse

50





Laser therapy

Features

product code	A-UL-AST-PHPS1	operation with applicators: scanning laser, cluster laser and point probes
color display with touch panel	7"	emission mode: continuous and pulse
independent treatment channels	1	adjustment of laser radiation power
manual mode	✓	asjacanon en accontación poner
disease entities selected by name	✓	duty factor
preset treatment programs database	✓	possibility of automatic treatment procedure repetition
user-defined programs database	✓	automatic laser radiation power test
user sequence database	✓	automatic calculation of time relative to treatment parameters - dose, power, duty factor, treatment area
favorite programs	✓	three modes of treatment field irradiation in scanning laser applicators
possibility of program names and user sequences edition	✓	dedicated modes for cooperation with optical fiber applicators
encyclopedia describing the treatment methodology	✓	optical fiber applicators for laserpuncture and ENT applications
statistics of performed treatment procedures	✓	three application adapters: 1 cm2, 5 cm2, DILA
buzzer sound volume regulation	✓	independent parameter settings for both sources
parameter setting / adjustment knob	✓	pilot beam indicating the application site

Preset treatment programs

built-in treatment programs, including:	
high power laser probe programs	50
IR point probe programs	38
R point probe programs	20
programs with Nogier frequency	8
programs with Voll frequency	30
cluster laser applicator programs	55
program sequences for scanning laser applicators	

Preset treatment sequences

user-defined sequences



Polaris HP S page 1 / 2



Laser therapy technical parameters

laser device class 4
treatment timer 1 s - 100 min

Laser therapy parameters - biostimulation laser point probes

red light laser point probes wavelength 660 nm maximum power of the red light point probes 80 mW infrared laser point probes wavelength 808 nm maximum power of the infrared point probes 400 mW power regulation 25%, 50%, 75%, 100% pulse mode frequency 1 - 5000 Hz duty factor in pulse mode 5 - 90%, impuls 50 us

Laser therapy parameters - scanning laser applicator

scanning laser applicator wavelength 808 & 660 nm maximum power of the scanning laser applicator 450 & 100 mW power regulation 50%, 100% pulse mode frequency 1 - 5000 Hz duty factor for scaning laser applicator pulse mode 75%

Laser therapy parameters - cluster laser applicator

cluster laser applicator wavelength 4x 808 nm & 5x 660 nm maximum power of the cluster laser applicator 4x 400 mW & 5x 40 mW power regulation 50%, 100% pulse mode frequency 1 -5000 Hz duty factor in pulse mode 5 - 90%, impuls 50 us

Laser therapy parameters - high power laser applicators

high power laser applicator wavelength

808 & 980 nm

peak power output

maks 18 W

average output power

maks 10 W

pulse mode frequency

1 - 10 000 Hz

duty factor in pulse mode

General technical parameters

dimensions $36.1 \times 30.4 \times 15.1 \text{ cm}$ device weight 6 kgpower supply, power consumption 230 V, 50 Hz, 130 W, 150 V

